

FOR PE PIPE FROM 20mm to 63 mm

MAIN FEATURES:

- The Male / Female reduction consists of a standard brass part which responds to the assembly of two parts with a thread at a distance of 2 nominal diameters.

- The male / female ring is suitable for any type of assembly of two parts by reducing the nominal diameter by several notches.
- The equal male double nipple is a connecting piece with threaded ends which is suitable for any assembly of two pieces of tap fittings, or which allows to connect two female fittings together, as well as a tap with a fitting and transform a fitting or a female output male output.
- The tee derivation allows a tapping made on the same drinking water network to be placed in a standby or blocked situation
- The male or female plugs are used to block any quicktightening fitting or other fitting, in order to temporarily transform it into a shutter

MALE / FEMALE REDUCTION ELEMENTS

MALE / FEMALE RING

DOUBLE MALE NIPPLE EQUAL

TEE DERIVATION

MALE PLUG

FEMALE PLUG

TECHNICAL SPECIFICATIONS:

Body : brass CW 602N - CuZn 36Pb2

Thread : gas thread ISO 228-1


Pressure tightness test : 16 bars











ALMA - MOROCCAN MANUFACTURER OF PUBLIC EQUIPEMENT - MMEP - S.A.

Had Soualem, Douar LAASILAT, Commune de Sahel, Ouled Hriz-Cercle de Berrechid-26400

Ph.: +212 5 22 99 51 52 - **Fax** : +212 5 22 99 49 50 **Email** : contact@alma.ma - **website** : www.alma.ma

