



CONNECTION ACCESSORIES

- QUICK-RELEASE FITTING

FOR PE PIPE FROM 20mm to 63 mm

MAIN FEATURES :

- Quick-release fitting with full-pass male clamping nut performing by mechanical tightening, the connection between the PE pipe with a female tapped body
- Sealing and assembly: a symmetrical rubber O-ring with anti-friction ring and three-tooth claw ring acting simultaneously to ensure self-locking and sealing of the connection by tightening the compression nut
- Fitting assembled and ready for interlocking of the pipe and tightening of the compression nut
- Permissible operating pressure : 16 bar



TECHNICAL SPECIFICATIONS :

Body:	brass CW 602N — CuZn 36Pb2
O-ring:	rubber EN 681-1
Anti-friction ring:	brass CW 602N — CuZn 36Pb2
Claw ring:	brass CW 602N — CuZn 36Pb2
Compression nut:	brass CW 602N — CuZn 36Pb2
Closed shutter pressure leak test:	16 bar
Tear resistance test	
Brinell hardness test	



ALMA – MOROCCAN MANUFACTURER OF PUBLIC EQUIPEMENT - MMEP - S.A.

Z.I. Had Soualem, Douar LAASILAT, Commune de Sahel, Ouled Hriz-Cercle de Berrechid-26400 MAROC.

ph.: +212 5 22 99 51 52 - Fax : +212 5 22 99 49 50

Email : contact@alma.ma – Website : www.alma.ma

